

# E-Series **EAHV** **AIR-TO-WATER** HEAT PUMP

High Performance with a Lower Carbon Footprint



**MODULAR AND SCALABLE**

Up to 300 RT with 6 units, **scalable to 1,200 RT** with 24 units per system.





## Operating Performance

- ◆ Heating: -20°C to 43°C
- ◆ Cooling: -15°C to 52°C
- ◆ Maximum Water Outlet Temp: 55°C
- ◆ 4 Ultra Quiet Inverter-Driven Compressors in Each Module
- ◆ High Turndown Ratio with Multiple Modules

## Modular Design

- ◆ Connect Up to 6 Units in a Group, 24 Units in a System
- ◆ Easy Integration with New Design or Retrofit Applications
- ◆ Compact Footprint for Individual or Multiple Modules
- ◆ Simple Hydraulic Connections with Option for Internal or External Header

## Operating Capacity

- ◆ 40 Tons / 150kW
- ◆ 50 Tons / 180kW



### COMMERCIAL BUILDINGS

Offices  
Retail  
Hotels



### INDUSTRIAL FACILITIES

Light Manufacturing Plants  
Distribution Centres  
Storage Warehouses



### INSTITUTIONAL BUILDINGS

Schools  
Community Centres  
Government Buildings